

## Thermo Scientific TruScan RM

Next Generation Handheld Raman for  
Raw Material Identification

With increasing regulatory pressures and the drive toward lean manufacturing, it is now more critical than ever to implement efficient ways to perform accurate incoming raw material identification.

With the Thermo Scientific TruScan RM analyzer, our next generation handheld Raman spectrometer, pharmaceutical manufacturers can obtain reliable material identity verification within seconds.



The Thermo Scientific TruScan RM analyzer is the next generation handheld Raman spectrometer for raw material identification and finished product inspection.

Our lightest, fastest and most portable analyzer is highly specific and performs rapid material identification at the point-of-need to decrease sampling costs and increase inventory turns. Designed for intuitive operation, its non-destructive point-and-shoot sampling principle facilitates rapid verification of a broad range of chemical compounds through sealed packaging to minimize the risk of contamination and exposure.

The TruScan® RM analyzer builds on the proven capability of the flagship TruScan analyzer, which is now used in hundreds of pharmaceutical manufacturing sites globally, to deliver a state-of-the-art optical platform paired with a revolutionary embedded analysis package. The analyzer also offers enhanced compliance features, as well as software and data management

functions, designed to facilitate workflow and optimize efficiency in tightly regulated environments.

### Key Benefits Include:

#### Fast

Overall performance enhancements provide faster PASS/FAIL results, and enable quicker method development and data synchronization.

#### Compliant

Enhanced 21 CFR Part 11 compliance security features, such as biometric log-in and optional password aging and complexity, allow users to customize the analyzer's security settings to exceed regulatory requirements.

#### Broad Material Coverage

State-of-the-art optics allow measurement of materials for which Raman analysis was traditionally considered too slow.

## Product Specifications

### Key Benefits (cont)

#### Smart

Built-in smart features, such as assisted signature acquisition and device qualification warnings, ensure successful material identification and prevent user error.

#### Easy to use

Enhanced user interface and improved functionality, such as consolidated batch reporting and intuitive workflow, make the analyzer consistent with current manufacturing processes.

#### Lightweight


Weighing less than 2 pounds (0.9kg), the analyzer is ergonomically designed to increase comfort and productivity during inspections.

#### Applications Include:

- Incoming raw material identity verification
- Counterfeit identification



The analyzer performs identification through sealed packaging to minimize the risk of contamination and exposure.



Once a measurement is complete, the analyzer provides a clear PASS/FAIL result within seconds.

## Thermo Scientific TruScan RM

|  |  |
|--|--|
| <b>Raman Spectrum Range</b>            | 250 to 2875 $\text{cm}^{-1}$   |
| <b>Spectral Resolution</b>             | 8 to 10.5 $\text{cm}^{-1}$ (FWHM) across range                                       |
| <b>Laser (excitation wavelength)</b>   | 785 nm $\pm$ 0.5 nm, 2 $\text{cm}^{-1}$ line width, stability $<0.1 \text{ cm}^{-1}$ |
| <b>Laser Output Power</b>              | 250 mW $\pm$ 25 mW   |
| <b>Collection Optics</b>               | NA = 0.33, 18 mm working distance; 0.2 to 2.5 mm spot size                           |
| <b>Exposure</b>                        | Automatic modes (12 ms minimum)  |
| <b>Battery</b>                         | Rechargeable internal lithium ion battery > 4 hours operation                        |
| <b>External Power Supply</b>           | DC Wall Adapter, 100-240 V AC 50/60 Hz   |
| <b>Weight</b>                          | 2 lb (0.9 kg)  |
| <b>Size</b>                            | 8.2 in x 4.2 in x 1.7 in (20.8 cm x 10.7 cm x 4.3 cm)                                |
| <b>Operating Temperature</b>           | -20 $^{\circ}\text{C}$ to +40 $^{\circ}\text{C}$ (continuous)                        |
| <b>Barcode Supported Symbolologies</b> | Most linear and 2D standards   |
| <b>Biometrics</b>                      | Fingerprint reader for easy login  |
| <b>Measurement Accessories</b>         | Vial holder, universal tablet holder   |
| <b>Compliance</b>                      | FDA 1040, 21 CFR part 11, CE certification   |



주식회사 드림 본사  
경기도 수원시 영통구 신원로 88  
(신동, 디지털융합타운) 103동 610호

TEL 031-695-6030 / 6020  
FAX 031-695-6045  
E-mail dream@dreamcorp.co.kr

구매 사무소  
경북 구미시 구미대로 350-27, 406  
(IT의료융합기술센터, 본관동)

TEL 054-461-6030  
FAX 054-461-6033  
E-mail dream@dreamcorp.co.kr

드림 베트남 법인  
24th floor, Block B Song Da  
Building, Pham Hung Street, My Dinh 1  
Ward, Nam Tu Liem District, Hanoi

TEL +84-243-200-9410  
FAX +84-243-200-9470  
E-mail dream\_vina@dreamcorp.co.kr



www.dreamcorp.co.kr

**Thermo**  
SCIENTIFIC